

# Tank-mix Sheet



# FLIPPER®

Please note that physical compatibilities may not be approved tank-mixes. The tests do not check for any adverse crop phytotoxicity or for the biological efficacy of the individual components when applied in a tank-mix. Bayer Crop Science gives no warranty and accepts no liability in respect of physical compatibilities; therefore, use is at grower's own risk.

All the requirements or restrictions on other product labels must be adhered to when tank-mixing with FLIPPER®. Contact Bayer Crop Science for full details.

FLIPPER® readily mixes with water and does not require vigorous agitation. Excessive use of an agitator may cause the formation of foam. Keep stirrer and mixer at minimum speed. When used in tank mix FLIPPER® must be added to the tank last.

FLIPPER® is physically compatible with only **ONE** of the following tank-mix selections:

Fungicides		
Agree 50 WG	Luna® Privilege	Signum
Bellis	Luna® Sensation	Sonata®
DiPel DF	Nativo®	Switch
Filan	Previcur® Energy	Sythane 20 EW
Folicur®	Rudis®	Thioproton
Fontelis	Serenade® ASO	Topas

Insecticides		
Batavia®	Movento®	Teppeki
Coragen	Naturalis-L	Tracer
Lepinox Plus	Steward	

Other		
Align*	TSCA†	
Omex Garland	X – Fusion•	



## Always follow the label instructions for water conditioners

\*Align Dose Rate: **0.1% v/v per 100ppm water hardness to bring water hardness to below 300ppm.** Bayer Crop Science has conducted limited efficacy testing and found the product to have a positive impact on the efficacy of FLIPPER in hard water (450ppm, 3 Ca:1 Mg), with no impact on selectivity.

**DO NOT exceed a maximum dose rate of 1% Align.**

† TSCA Dose Rate: Add Tri-sodium salt of citric acid in the spray tank to water before adding FLIPPER to bring back water hardness to below 300 ppm (16.8 dGH).

Water hardness value 300 – 450 ppm (25 dGH) - The amount of Tri-sodium salt of citric acid to be added: Up to 2 g / lt of water, or 2 kg / 1000 lt of water

Water hardness value > 450 ppm (25 dGH) – The amount of Tri-sodium salt of citric acid to be added is: Up to 45 g / 10 ppm (0.5 dGH ) in 1000 lt of water. For example, for a water hardness of 660 ppm (37 dGH ) add 3 kg of trisodium citrate dehydrate (trisodium salt of citric acid) in 1000 lt of water.

• X-Fusion Dose Rate: 0.2% of spray volume in normal UK hard water. Where water hardness is higher than 400ppm consult De Sangosse Ltd for appropriate dose rates.

### X-Fusion Rate

% Rate	ml per 100 litres	ml per 200 litres
0.2	200	400
0.25	250	500
0.3	300	600

### Recent Changes

27/3/2020	2-way mixes with Batavia®, DiPel DF, Luna® Privilege, Luna® Sensation, Nativo®, Omex Garland, Rudis®, Serenade® ASO and Sonata® added.
02/06/2020	2-way mixes with Align* and Systhane 20 EW added. Information on water hardness and water softener testing for Align* added.
30/06/2020	2-way mix with TSCA† added. . Information on water hardness and water softener testing for TSCA† added.
28/07/2020	2-way mix with X-Fusion• added. Information on water hardness and dose rates added for X-Fusion•

